



PRODUCT STANDARD SPECIFICATIONS

Product Standard Specifications For

Candid Cowhide **Performance Rating = 4.0**

Product: Candid Cowhide

Description: Top Grain, Cowhide, Aniline Dyed

Average Hide Size: 55 – 60 SF

Thickness: 1.1mm (+/- 0.2mm)

Testing:

Meets the following standards:

Flammability: (Must be Specified on the PO)
IMO Finishes & Furnishings (2010 FTP) MSC 88/26
Part 5: Surface Flammability [was A.653 (16)]
Part 8: Upholstered Furniture [was A.652 (16)]
FAR 25.853(a)(1)(ii) - 12 Second Vertical
FAR 25.853(a)(1)(i) - 60 Second Vertical
Cal TB 117
NFPA 260 Class 1
BS5852 Crib 5

Water Spotting: IUF420 - No Staining

Crocking: ASTM D5053 - minimum 3 on AATCC Greyscale

Federal Blocking: ASTM D6116 - No Adhesion of Finish

Arm Rub Welt: Townsend LM7 - No Finish Break Through

Adhesion: Townsend LM5 - No Removal of Finish

Taber: ASTM D3884 H18 250g 300 Cycles – No Change in Color

Accelerated Aging: Townsend LM2 - minimum 3 on AATCC Greyscale,
No Cracking

Revision 1
