

townsend PRODUCT STANDARD SPECIFICATIONS **SPECIFICATIONS**

Product Standard Specifications For

Karma Cowhide Performance Rating = 4.0

Product: Karma Cowhide

Description: Top Grain, Cowhide, Aniline Dyed Average Hide Size: 40 – 45 SF Center Cut or 25 SF Side

Thickness: 1.1mm (+/- 0.2mm)

Testing:

Meets the following standards:

Flammability: (Must be Specified on the PO)

IMO Finishes & Furnishings (2010 FTP) MSC 88/26

Part 5: Surface Flammability [was A.653 (16)] Part 8: Upholstered Furniture [was A.652 (16)]

FAR 25.853(a)(I)(ii) - 12 Second Vertical FAR 25.853(a)(I)(i) - 60 Second Vertical

Cal TB 117

NFPA 260 Class 1 BS5852 Crib 5

Water Spotting: IUF420 - No Staining

Crocking: ASTM D5053 - minimum 3 on AATCC Greyscale

Federal Blocking: ASTM D6116 - No Adhesion of Finish

Arm Rub Welt: Townsend LM7 - No Finish Break Through

Adhesion: Townsend LM5 - No Removal of Finish

Taber: ASTM D3884 H18 250g 300 Cycles – No Change in

Color

Townsend LM2 - minimum 3 on AATCC Greyscale, **Accelerated Aging:**

No Cracking

Revision 2